

1585CW-2

S H E A T H I N G T A P E



Venture Tape 1585CW-2 is a polypropylene sheathing tape coated with an aggressive acrylic pressure sensitive adhesive (PSA) designed for use as a closure system and vapor seal on all interior and exterior sheathing materials.

Venture Tape 1585CW-2 exceeds most building code requirements and can be used for new construction as well as repair on all vapor barrier materials.

Available in red and white, Venture Tape 1585CW-2 is the highest performing, highest value product on the market today.

Features & Benefits

- High performance sheathing tape installs and performs well over a wide temperature range
- Excellent vapor barrier tape on polyethylene film
- Performs well as a seam tape on extruded foam products such as **Styrofoam®** and **Foamular®**
- Applies to all major housewraps including **Tyvek®** and **Typar®**
- Approved by Georgia Pacific as a sealing tape on **Dens Glass Gold®** as well as other sheathing brands

Synoblen® is a registered trademark of Dow Corporation
Foamular® is a registered trademark of Owens Corning Fiberglas Corporation
Tyvek® is a registered trademark of E.I. DuPont de Nemours & Co. Incorporated
Typar® is a registered trademark of Warriner Incorporated
Dens Glass Gold® is a registered trademark of Georgia Pacific Gypsum Corporation

Test	Typical Value	Test Method
Product Thickness (total)	3.0 mils	PSTC-133
Carrier Thickness	1.5 mils	PSTC-133
Adhesive Thickness	1.5 mils	PSTC-133
Peel Adhesion - Stainless Steel	65 oz/in	PSTC-101
Peel Adhesion - Polyethylene	16 oz/in	PSTC-101
Peel Adhesion - Tyvek®	28 oz/in	PSTC-101
Shear Strength	>96 hours	PSTC-107
Tensile Strength	20 lb/in width	PSTC-131
Elongation	136 %	PSTC-131
WVTR	0.16 g/100 in ² /24 hr	ASTM E-96
Application Temperature	-20 °F to 120 °F	
Service Temperature	-40 °F to 275 °F	

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Product Configurations

Width (in.)	Length (LY)	Rolls/Case
1 7/8	72	16
2 1/2	72	12

Contact Venture Tape today for a complete list of products or a free sample

Toll Free USA 800-343-1076

From Canada 800-544-1024

From United Kingdom 0-800-962-957

From Australia 1-800-122-797

www.venturetape.com

USA

Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065

Europe

Venture Tape Europe Corp.
Units 5 - 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 5RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia

Venture Tape Australasia, Pty., Ltd.
90A Northgate Drive
Thomastown 3074 Victoria
Australia
(03) 9464 2089
FAX (03) 9464 7268